

**Designed For
Skid Steers &
Farm Tractors.**



**For A Quote
Call Us At:
(615) 707-2278**

Limb Beaver 4 Series

Limb Beaver delivers a full line of heavy-duty brush and limb-removal attachments designed to outperform in the toughest vegetation conditions. Each model—built for skid steers, tractor loaders, excavators, and boom mowers—is precision-engineered to cut, clear, and control overgrowth with speed and accuracy.

LB 4

From dense brush and low-hanging limbs to overhang, saplings, and small trees, Limb Beaver attachments are built to tackle what standard equipment can't. Their rugged construction, powerful cutting systems, and operator-friendly design make them essential tools for maintaining everything from roadside corridors to remote trails.

Highway departments, county crews, farmers, hunting clubs, land managers, and property owners rely on Limb Beaver products to keep roadsides, easements, trails, lakeshores, and field edges clear and safe. Whether you're managing miles of right-of-way or reclaiming heavily overgrown acreage, Limb Beaver attachments deliver consistent performance and dependable results.

4 Foot Limb Trimming & Brush Clearing Attachment

LB 4SS for Skid Steers

- 48 inch cutting path
- Rotor speed of 3,000 RPM
- Cutting height up to 18 feet
- Cuts limbs up to 6 inches in diameter
- Tilt up to 45 degrees below horizontal position
- Offset vertical reach of 92 inches from center
- Offset to horizontal reach of 140 inches
- 90 degree swing from center in both directions
- Side vertical raised height of 216 inches
- Out front vertical raised height of 250 inches
- 34 double edge fixed teeth
- Weighs 950 pounds
- Hydraulic flow of 15 to 25 GPM



LB 4TR for Tractor Loaders

- 48 inch cutting path
- Rotor speed of 3,000 RPM
- Cutting height up to 70 inches plus pin height
- Cuts limbs up to 6 inches in diameter
- Hydraulic flow of 15 to 25 GPM
- Tilt up to 45 degrees below horizontal position
- Offset vertical reach of 92 inches from center
- Offset to horizontal reach of 140 inches
- 90 degree swing from center in both directions
- Side vertical raised height of 216 inches
- Out front vertical raised height of 250 inches
- Optional hydraulic swing
- 34 double edge fixed teeth
- Weighs 950 pounds



LB 4EX for Excavators & Boom Mowers

- 48 inch cutting path
- Rotor speed of 3,000 RPM
- Cutting height determined by excavator/boom mower
- Cuts limbs up to 6 inches in diameter
- Hydraulic flow of 15 to 25 GPM
- 34 double edge fixed teeth
- Weighs 400 pounds



Limb Beaver 4 Series

LB 4SS for Skid Steers

LB 4TR for Tractor Loaders

LB 4EX for Excavators
& Boom Mowers



Applications

- ▲ Encroaching or Overhanging Limb and Brush
- ▲ Farm Fields
- ▲ Trails
 - Snowmobile
 - Side by Side
 - Walking
- ▲ Right of Ways
 - Pipeline
 - Electric
 - Roads
 - Railroads
 - City Streets
- ▲ Line of Sight
- ▲ Easements
- ▲ Lake Side
- ▲ Creeks and Rivers
- ▲ Golf Courses
- ▲ Hunt Clubs
- ▲ Fence Lines
- ▲ Parks
- ▲ Recreational Areas
- ▲ Forestry Service



For **Video** - www.youtube.com/LimbBeaver

For **More Info** - www.LimbBeaver.com

For a **Quote** - Call Us At: (615) 707-2278

Limb Beaver

Thompson Station, TN 37179

Toll Free (844) 697-5505 • Sales@LimbBeaver.com • www.LimbBeaver.com